

# BWM 200+ capillary matting

Standard capillary matting, made from 100% recycled synthetic fibers.  
Does not contain Jute or cotton.

The BWM 200+ capillary matting offers a high water capacity, in combination with a low capillary effect. An excellent choice for growers who renew the cultivation system every year. The BWM capillary matting is also very suitable for use on sales tables.

In terms of weight, the BWM 200+ is the lightest version in the [BWM capillary mattings segment](#). And therefore the most advantageous in terms of price.

## **BWM 200+**

Weight: 200 gr/m<sup>2</sup>  
Watercapaciteit: 3,0 tot 4,0 liter/m<sup>2</sup>

Lengths: 40 and 50 meter  
Widths: 8 cm to 250 cm

## **Customization:**

Henofa has punching and cutting machines to provide customization, for selling tables, cultivation gutters, container fields and deviating lengths. For more information, please send us a email on [info@henofa.com](mailto:info@henofa.com).

Besides the standard version, the BWM 200+ is also available with foil and groundcover.

[BWM 200 + BF](#)

[BWM 200 + WF](#)

[BWM 200 + SF](#)

[BWM 200 + BGC](#)

| Technical specification                           | Non-woven capillary matting |                   |
|---|-----------------------------|-------------------|
| <u>Composition:</u>                               | <u>Nominal:</u>             | <u>Tolerance:</u> |
| Fiber composition                                 | Recycling fibers            |                   |
| Weight (gr/m <sup>2</sup> )                       | 200                         | 5%                |
| Thickness (mm)                                    | 2,0                         | 5%                |
| Tensile-strength (kg/cm <sup>2</sup> ) Length-dry | 3,0                         |                   |
| Tensile-strength (kg/cm <sup>2</sup> ) Width-dry  | 3,0                         |                   |
| Tensile-strength (kg/cm <sup>2</sup> ) Length-wet | 3,0                         |                   |
| Tensile-strength (kg/cm <sup>2</sup> ) Width-wet  | 3,0                         |                   |
| Absorption capacity (ltr/m <sup>2</sup> )         | 3,0 to 4,0                  |                   |
| Standard Length                                   | 40 or 50 meter              |                   |
| Colour  | Multi-colour                |                   |