

Klavermat 200 + BGC capillary matting

The Klavermat 200 capillary matting is a quality product that is produced from 100% new, high-quality synthetic fibers.

Every fiber has exactly the same properties. In combination with the unique 3dimensional structure of the mat, this results in a very good capillary effect. A wide range of crops can be grown on the Klavermat.

The Klavermat 200 capillary matting is distinguished by its robustness, chemical resistance, constant operation and long service life. With the Klavermat it is possible to grow crops in a reproducible way and to quickly switch between different crops.

The black ground cover is needled directly onto the irrigation mat, resulting in a strong and robust product. The needling of fibers on the ground cloth creates a perfect transition between fibers and covering materials.

The combined 2-layer product offers significant savings in time and installation costs, and it is also easy to clean. For this reason, it is frequently used on sales tables.

Functions of the ground cover;

- Prevention of root growth
- Prevention of algae growth
- Prevent unnecessary evaporation of water
- Extending the life of the capillary matting
- Provide protection against mechanical influences, such as sweeping.

Klavermat 200 + BGC

Weight:	200 gr/m²
Ground cover:	Black - 100 gr/m ²
Water capacity:	2,0 to 2,5 liter/m ²

Lenght:	75 meter	
Width:	8 cm to 250 cm	

Customization:

Henofa has punching and cutting machines to provide customization, for selling tables, cultivation gutters, container fields and deviating lengths. For more information, please send us a email on <u>info@henofa.com</u>.

HENOFA BV - Het Wegdam 13 - 7496 CB Hengevelde-NL - Tel. +31 547 334249 - Fax +31 547 334253 ABN AMRO Bank Hengelo 46 12 48 913 - IBAN nr. NL18 ABNA0461248913 BIC/SWIFT code ABNANL2A KvK Enschede 06069701 - BTW/VAT nr. 8021 36 084 B01 internet: www.henofa.com - e-mail: info@henofa.com



Technical specification	Non-woven capillary matting		
Composition:	Nominal:	Tolerance:	
Fiber composition	100% new synthetic	100% new synthetic fibers	
Weight (gr/m ²)	200	5%	
Thickness (mm)	4,0	5%	
Tensile-strength (kg/cm ²) Length-dry	2,3		
Tensile-strength (kg/cm ²) Width-dry	2,8		
Tensile-strength (kg/cm ²) Length-wet	2,1		
Tensile-strength (kg/cm ²) Width-wet	2.7		
Absorption capacity (ltr/m ²)	2,0 to 2,5		
Standard Length	75 meter		
Colour	Black		

HENOFA BV - Het Wegdam 13 - 7496 CB Hengevelde-NL - Tel. +31 547 334249 - Fax +31 547 334253 ABN AMRO Bank Hengelo 46 12 48 913 - IBAN nr. NL18 ABNA0461248913 BIC/SWIFT code ABNANL2A KvK Enschede 06069701 - BTW/VAT nr. 8021 36 084 B01 internet: www.henofa.com - e-mail: info@henofa.com