

HENO ISOFOILBubble Foil

Our insulation range consists of the product Heno Isofoil bubble wrap. Heno Isofoil can be used directly as a professional insulation material and / or as a protection product against external influences.



Areas of application

- Insulating horticultural greenhouses, floors, roofs and sheds / garages.
- (Temporary) sealing of construction projects in the cold winter months.




UV resistant



3 layers



R-value



Composition

Heno Isofoil is made up of three layers of high-quality PE bubble foil, all sides are sealed so you are assured of a high-quality and airtight material.

Its high insulation value provides a significant improvement in comfort and energy savings.



HENO ISOFOIL Bubble Foil

Advantages of Heno Isofoil

- Heat and cold resistance
- Highly transparent and UV resistant
- Easy to process
- Energy savings of up to 40% can be achieved





Properties Heno Isofoil

Number of layers:

0,147 m²K/W R-value: plano or folded Folding method:

50 µm Foil thickness: **Bubble diameter:** 31,7 mm **Bubble height:** 13,7 mm **Bubble height tolerance +-:** 10% Weight per m²: 106 g/m² Weight tolerance: ±7% **Storage temperature:** (5-50°C) **Processing temperature:** (5-50°C) Thermal decomposition:

We would like to point out that the Heno Isofoil bubble foil remains 12 months UV-resistant in a central European climate.

>360 °C

Special dimensions (sealed): **Standard dimensions:**

1,20 x 50 Meter (plano) 3,00 x 50 Meter (folded) 1,50 x 50 Meter (plano) 3,50 x 50 Meter (folded) 2,00 x 50 Meter (plano) $4,00 \times 50$ Meter (folded) 2,40 x 50 Meter (plano) 4,80 x 50 Meter (folded)