

BWM 200 + BGC capillary matting

Standard capillary matting, made from 100% recycled synthetic fibers. Equipped with a black groundcover. Contains no natural fibers such as Jute or Cotton.

The black groundcover is needled directly onto capillary matting, resulting in a strong and robust product. The needling of fibers on the groundcover creates a perfect transition between fibers and covering materials.

The combined 2-layer product offers significant savings in time and installation costs, and it is also easy to clean. For this reason, it is frequently used on sales tables.

Functions of the groundcover:

- ❖ Preventing root growth in the capillary matting
- ❖ Prevents the growth of algae
- ❖ Prevention of unnecessary evaporation of water
- ❖ Extending the life of the capillary matting
- ❖ Provide protection against mechanical influences, such as sweeping or walking

BWM 200 + BGC:

Weight: 200 gr/m²
 Groundcover: Black - 100 gr/m²
 Water capacity: 3,0 to 4,0 liter/m²

Lengths: 40 and 50 meter
 Widths: 8 to 250 cm

Customization:

Henofa has punching and cutting machines to provide customization, for selling tables, cultivation gutters, container fields and deviating lengths. For more information, please send us a email on info@henofa.com.

Technical specification	Non-woven capillary matting	
Composition:	Nominal:	Tolerance:
Fiber composition	Recycling fibers	
Weight (gr/m ²)	300	5%
Thickness (mm)	2,0	5%
Tensile-strength (kg/cm ²) Length-dry	3,0	
Tensile-strength (kg/cm ²) Width-dry	3,0	
Tensile-strength (kg/cm ²) Length-wet	3,0	
Tensile-strength (kg/cm ²) Width-wet	3,0	
Water capacity (ltr/m ²)	3,0 to 4,0	
Standard Length	40 or 50 meter	
Colour	Multi-colour	