

BWM 400 + BF capillary matting

Standard capillary matting, made from 100% recycled synthetic fibers. Equipped with a black anti algae foil, with a thickness of 30 μm . Contains no natural fibers such as Jute or Cotton.

BWM 400 + BF capillary matting offers a high water capacity in combination with a low capillary function. BF stands for black anti algae foil, the foil is wrapped loosely on the capillary matting and has a fine perforation.

Functions of the black anti algae foil:

- Preventing root growth in the capillary matting
- Prevents the growth of algae
- Prevention of unnecessary evaporation of water
- Extending the life of the capillary matting
- Provide protection against mechanical influences, such as sweeping or walking

BWM 400 + BF:

Weight: 400 gr/m² Anti-algae foil: Black - 30 μ m Water capacity: 5,0 to 6,0 liter/m²

Lengths: 40 and 50 meter Widths: 8 to 250 cm

Customization:

Henofa has punching and cutting machines to provide customization, for selling tables, cultivation gutters, container fields and deviating lengths. For more information, please send us a email on info@henofa.com.

Technical specification	Non-woven capill matting	Non-woven capillary matting	
Composition:	Nominal:	Tolerance:	
Fiber composition	Recycling fibers		
Weight (gr/m²)	450	5%	
Anti-algae foil	Black, 30 µm		
Thickness (mm)	5,0	5%	
Tensile-strength (kg/cm²) Length-dry	6,0		
Tensile-strength (kg/cm²) Width-dry	6,0		
Tensile-strength (kg/cm²) Length-wet	6,0		
Tensile-strength (kg/cm²) Width-wet	6,0		
Absorption capacity (ltr/m²)	5,0 to 6,0		
Standard Length	40 or 50 meter	40 or 50 meter	
Colour	Multi-colour		